

AMERICOLON® APVC6621



Homopolymer/Pipe Grade Resin

APVC6621 is a medium-low molecular weight PVC homopolymer designed primarily for rigid extrusion applications. This product has excellent dry flow characteristics, making it desirable for dry blending applications where uniform feed rate to an extruder is important.

Suggested Applications: Pipe and Conduit.		
Properties	Test Method	Typical Value
Relative Viscosity	estimated	2.15
Inherent Viscosity	ASTM D-5225	0.91
K-Value	estimated	65
Volatiles (%)	ASTM D-6980	0.30
Bulk Density (lbs/ft3)	ASTM D-1895	32.5
(g/cc)		0.52
Sieve Analysis	Malvern	
% thru 40 Mesh		99.9
% thru 200 Mesh		5.0
Residual VCM (ppm)	GC Head Space Method	1.0
Contamination Count	OCS per 100g	40

Effective as of November 2017

inquiries regarding this data sheet should be addressed to: 11824 Jollyville Rd Austin, TX 78759 · Phone (800) 729 5417 · Fax: (512) 992 0225

The information and recommendation in this publication are, to the best of knowledge, reliable. Suggestions concerning uses are only the opinion of AMERICORP INTERNATIONAL LTD, U.S.A. and users should perform their own tests to determine the suitability of this products for their own particular purposes. However, because of the numerous factors affecting the results, AMERICORP INTERNATIONAL LTD, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSES, other than that the material conforms to the applicable current standard specifications statement herein, therefor, should not be construed as representations or warranties. The responsibility of AMERICORP INTERNATIONAL LTD, U.S.A. for claims arising out of breach warranty, negligence, and strict liability or otherwise is limited to the purchase price of the material. Statement concerning the use of the products of AmeriCorp described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed