

Ethanol (99.9%)

Test Description	Test Method	Unit of Measure	Specification
Appearance	Visual	-	Clear & Bright
Density @ 20/20°C (Vac)	ASTM D 4052	Kg/I	0.7892
Colour	ASTM D 1209	Pt/Co	LT 5
Distillation			
IBP	ASTM D 1078	° C	78.2
DP	ASTM D 1078	° C	78.9
Acidity as Acetic Acid	ASTM D 1613	% Weight	0.0018
Water Content	ASTM E 1064	% Weight	0.04
Suspended Matter	Visual	-	Nil
Water Solubility	ASTM D 1722	-	Miscible
Purity	GC	% Weight	99.9
Methanol	GC	% Weight	<0.01
n-Propanol	GC	% Weight	<0.01
Aromatic Hydrocarbon	GC	% Weight	<0.01

Comments: Physical properties are not monitored constantly.

Issue of revision date: 21.10.2020

_

Spec Version:1

Any inquiries regarding this data sheet should be addressed to: 11824 Jollyville Rd Austin, TX 78759 · Phone (800) 729 5417 · Fax: (512) 992 0225

The information and recommendation in this publication are, to the best of knowledge, reliable. Suggestions concerning uses are only the opinion of AMERICORP INTERNATIONAL LTD, U.S.A. and users should perform their own tests to determine the suitability of this products for their own particular purposes. However, because of the numerous factors affecting the results, AMERICORP INTERNATIONAL LTD, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSES, other than that the material conforms to the applicable current standard specifications statement herein, therefor, should not be construed as representations or warranties. The responsibility of AMERICORP INTERNATIONAL LTD, U.S.A. for claims arising out of breach warranty, negligence, and strict liability or otherwise is limited to the purchase price of the material. Statement concerning the use of the products of AmeriCorp described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed

©Americorp International LTD, U.S.A

Americorp Petrochemical® is a registered tradename of ACI U.S.A