

## AMERICOLENE® APC2050-IM

# AMERICOLENE

### High Density Polyethylene Injection Molding (HDPE-IM)

Americolene<sup>®</sup> APC2050-IM is a generic, prime, narrow molecular weight high density polyethylene copolymer intended for applications requiring a glossy finish and reasonably good impact strength and rigidity. It is characterized by a high melt index which allows easy processing of medium to thin walled articles. This material meets the Food and Drug Administration requirements of 21 CFR 177.1520.

### **Nominal Physical Properties:**

PROPERTY	ASTM TEST METHOD	UNIT	VALUE
Typical Resin Properties for APC2050-IM:			
Melt Index	D1238	g/10 min.	20.0
Density	D4883	g/cc	0.9530
Tensile Strength (2 in/min)	D638		
@ Yield		27.6 MPa	4,000 psi
@ Break		14.8 MPa	2,140 psi
Elongation (2 in/min)	D638		
@ Yield		9.1 %	9.1 %
@ Break		>200 %	>200 %
Flexural Modulus	D790A		
2% Secant Method		1,227 MPa	178,900 psi
Tangent Method		1281 Mpa	185,800 psi
Notched Izod Impact Strength	D256	2.77 kJ/m2	0.53 ft-lbf/in
Hardness	D2240		
Shore D		66	66
Vicat Softening Point	D1525	125 C	257 F
Brittleness Temperature	D746	<-70 C	<-94 F
Heat Defection Temperature	D648		
@ 66 psi psi (455 kPa)		72 C	162 F
Environmental Stress Crack Resistance	D1693		
Condition B, 100% Igepal, F50 (hrs.)		1.8	1.8

\* MD / TD

Published 02/01/13, Revised 11/10/21

#### Any inquiries regarding this data sheet should be addressed to: 11824 Jollyville Rd Austin, TX 78759 · Phone (800) 729 5417 · Fax: (512) 992 0225

The information and recommendation in this publication are, to the best of knowledge, reliable. Suggestions concerning uses are only the opinion of AMERICORP INTERNATIONAL LTD, U.S.A. and users should perform their own tests to determine the suitability of this products for their own particular purposes. However, because of the numerous factors affecting the results, AMERICORP INTERNATIONAL LTD, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSES, other than that the material conforms to the applicable current standard specifications statement herein, therefor, should not be construed as representations or warranties. The responsibility of AMERICORP INTERNATIONAL LTD, U.S.A. for claims arising out of breach warranty, negligence, and strict liability or otherwise is limited to the purchase price of the material. Statement concerning the use of the products of AmeriCorp described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed