

## AMERICOLENE® PPH12-IM

## *AMERICOLENE*

## Homopolymer for General Purpose Injection Molding

## **Technical Data Sheet**

AMERICOLENE® PPH12-IM is a medium viscosity, highly isotactic, polypropylene homopolymer designed for various general purpose injection molding applications such as closures, small appliances, housewares and toys. It contains a unique combination of stabilizers, which provides excellent processability with good stiffness, environmental stress crack resistance, heat performance and minimal odor & taste.

AMERICOLENE® PPH12-IM meets all requirements of the U. S. Food and Drug Administration as specified in 21 CFR 177.1520, covering safe use of polyolefin articles and components of articles intended for direct food contact.

NOMINAL RESIN PROPERTIES	NOMINAL VALUE (ENGLISH)	NOMINAL VALUE (SI)	METHO D
Melt Flow Rate, I2 @ 230°C	12.0	g/10 min	D1238
Density	0.9	g/cm3	D1505
Tensile Strength at Yield (50 mm/min)	4,800	psi	D638
Elongation at Yield (50 mm/min)	8	%	D638
Flexural Modulus (1.3 mm/min), 1% Secant	180,000	psi	D790
Rockwell Hardness	105	R Scale	D785
Notched Izod Impact Strength 73°F	0.6	ft-lb/in	D256
Heat Deflection Temperature @ 66 psi	100	°C	D648

Note: Specimens were injection molded according to the conditions specified in ASTM D4101. Published 02/01/13, Revised 11/10/21

Any inquiries regarding this data sheet should be addressed to: 11824 Jollyville Rd Austin, TX 78759 · Phone (800) 729 5417 · Fax: (512) 992 0225

The information and recommendation in this publication are, to the best of knowledge, reliable. Suggestions concerning uses are only the opinion of AMERICORP INTERNATIONAL LTD, U.S.A. and users should perform their own tests to determine the suitability of this products for their own particular purposes. However, because of the numerous factors affecting the results, AMERICORP INTERNATIONAL LTD, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSES, other than that the material conforms to the applicable current standard specifications statement herein, therefor, should not be construed as representations or warranties. The responsibility of AMERICORP INTERNATIONAL LTD, U.S.A. for claims arising out of breach warranty, negligence, and strict liability or otherwise is limited to the purchase price of the material. Statement concerning the use of the products of AmeriCorp described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed