

AMERICOLENE® LL69181A



Linear Low Density Polyethylene Hexane Copolymer for Film Grade

Americolene® LL69181A is a Hexene-based film grade linear low density. The resin exhibits excellent toughness and strength when drawn down to thin gauges.

Suggested Applications:

General Purpose Blow Film Industrial Packaging Industrial Liners Garment Bags Co-Extrusion Film

Nominal Physical Properties:

PROPERTY	TEST METHOD	UNIT	VALUE
Density	D1505	g/cc	0.918
Melt Index, Condition E, 190°C/2.16 kg	D1238	g/10 min	1.0
Slip		-	1350 ppm
Antiblock			6500 ppm
Dart	D1709	g/mil	190
Gloss (45°)	D2457	-	35
Haze	D1003	%	22

^{*} MD/TD

Note: FilmProperties measured on 0.8 mil (20 micron) cast film extruded at 320 fpm with a melt temperature at 520°F. and melt curtain of 1.0 inch.

Actual film properties may vary depending on operating conditions and additive packages. Film properties are not intended to be used as specifications.

Published 03/01/13, Revised 02/18

Any inquiries regarding this data sheet should be addressed to: 11824 Jollyville Rd Austin, TX 78759 · Phone (800) 729 5417 · Fax: (512) 992 0225

The information and recommendation in this publication are, to the best of knowledge, reliable. Suggestions concerning uses are only the opinion of AMERICORP INTERNATIONAL LTD, U.S.A. and users should perform their own tests to determine the suitability of this products for their own particular purposes. However, because of the numerous factors affecting the results, AMERICORP INTERNATIONAL LTD, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSES, other than that the material conforms to the applicable current standard specifications statement herein, therefor, should not be construed as representations or warranties. The responsibility of AMERICORP INTERNATIONAL LTD, U.S.A. for claims arising out of breach warranty, negligence, and strict liability or otherwise is limited to the purchase price of the material. Statement concerning the use of the products of AmeriCorp described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed