

AMERICOLENE® BC112-APT



CRYSTALLINE POLYETHYLENE TEREPHTHALATE (PET)

DESCRIPTION

BC212 is a crystalline, high molecular weight thermoplastic polymer made by continues melt-phase polymerization processfollowed by solid-state polymerization. BC212 is specially formulated bottle grade PET, characterized by high I.V and low acetaldehyde. The high I.V. confers goodmechanical properties; high burst strengths and reduced bottle distension after filling.

TYPICAL APPLICATIONS

BC212 is especially suitable for the production of bottles for carbonated drinks. The high I.V. gives the bottle the extra mechanical strength required in hot countries due to the high pressure from carbonation. It can also be used for bottles for non-carbonated and other packaging applications, e.g. edible oil & thermoformed packaging.

TYPICAL PROPERTY VALUES

PROPERTIES	TYPICAL VALUES	UNITS	TEST METHODS
PHYSICAL PROPERTIES			
Intrinsic Viscosity (1)	0.84 ± 0.02	dl/g	AMERICOLENE method
DEG Content	<1.5	Wt. %	AMERICOLENE method
Crystalline Density	<1390	kg/m³	AMERICOLENE method
Moisture Content (2)	<0.35	Wt. %	AMERICOLENE method
POLYMER PROPERTIES			
Acetaldehyde	<1	ppm	AMERICOLENE method
Color (L)	89 ± 4.0	L-value	IRC 0051
Color (b)	-1.5 ± 2.0	b-value	IRC 0051
Dust Content	<0.01	Wt. %	AMERICOLENE method
Bulk Density	850 ± 10	kg/m³	ASTM D1895

Any inquiries regarding this data sheet should be addressed to: 11824 Jollyville Rd Austin, TX 78759 · Phone (800) 729 5417 · Fax: (512) 992 0225

The information and recommendation in this publication are, to the best of knowledge, reliable. Suggestions concerning uses are only the opinion of AMERICORP INTERNATIONAL LTD, U.S.A. and users should perform their own tests to determine the suitability of this products for their own particular purposes. However, because of the numerous factors affecting the results, AMERICORP INTERNATIONAL LTD, U.S.A. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSES, other than that the material conforms to the applicable current standard specifications statement herein, therefor, should not be construed as representations or warranties. The responsibility of AMERICORP INTERNATIONAL LTD, U.S.A. for claims arising out of breach warranty, negligence, and strict liability or otherwise is limited to the purchase price of the material. Statement concerning the use of the products of AmeriCorp described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed